

## TECHNICKÉ PARAMETRE

### MENIČ

|                             |                                 |                               |                             |
|-----------------------------|---------------------------------|-------------------------------|-----------------------------|
| SKU                         | MOD-10KTL3-XH<br>MOD-6KTL3-XH   | Degree of protection (IP)     | IP66                        |
| DC Switch                   | Yes                             | Suitable for outdoor mounting | Yes                         |
| Warranty in Years           | 10                              | Surge protection              | Type II DC & AC             |
| Inverter type               | String                          | Display                       | Yes                         |
| Smart                       | Hybrid                          | WiFi                          | Optional                    |
| Number of phases            | 3 phase                         | Ethernet                      | Optional                    |
| Max. DC- input capacity (W) | 10KTL3 - 20000<br>6KTL3 - 12000 | Width (mm)                    | 425                         |
| AC-nominal output power     | 10KTL3 - 11000<br>6KTL3 - 6600  | Height (mm)                   | 387                         |
| Country of manufacture      | China                           | Depth (mm)                    | 10KTL3 - 178<br>6KTL3 - 147 |
| Number of MPPT              | 2                               | Weight (kg)                   | 10KTL3 - 14<br>6KTL3 - 12.5 |

### BATERKY

|                     |             |                          |          |
|---------------------|-------------|--------------------------|----------|
| Product ref.        | ARK 2.5H-A1 | Max. depth of discharge  | 90%      |
| Width               | 650 mm      | Nominal battery capacity | 2.56 kWh |
| Height              | 200 mm      | Max. input voltage DC    | 51.2 V   |
| Depth               | 250 mm      | Usable battery capacity  | 2.3 kWh  |
| Number of phases    | 3           | Series                   | ARK      |
| Ambient temperature | -10 +55 °C  | Made in                  | China    |
| Type of voltage     | DC          | Units per pallet         | 12       |

### PANELY

|                  |         |                               |               |
|------------------|---------|-------------------------------|---------------|
| Product ref.     | JaSolar | Type                          | Mono PERC     |
| STC Power Rating | 545W    | Output Terminal Type          | MC Type 4     |
| Peak Efficiency  | 21.09%  | Output Cable Wire Length      | 1,300mm       |
| Power Tolerances | 0%/+5%  | Frame Color / Backsheet Color | Clear / White |
| Imp              | 13.04A  | Length                        | 2,279mm       |
| Vmp              | 41.8V   | Width                         | 1,134mm       |
| Isc              | 13.93A  | Depth                         | 35mm          |
| Voc              | 49.75V  | Weight                        | 28.6kg        |

## TECHNICKÉ PARAMETRE

### MENIČ

|                             |                                 |                               |                             |
|-----------------------------|---------------------------------|-------------------------------|-----------------------------|
| SKU                         | MOD-10KTL3-XH<br>MOD-6KTL3-XH   | Degree of protection (IP)     | IP66                        |
| DC Switch                   | Yes                             | Suitable for outdoor mounting | Yes                         |
| Warranty in Years           | 10                              | Surge protection              | Type II DC & AC             |
| Inverter type               | String                          | Display                       | Yes                         |
| Smart                       | Hybrid                          | WiFi                          | Optional                    |
| Number of phases            | 3 phase                         | Ethernet                      | Optional                    |
| Max. DC- input capacity (W) | 10KTL3 - 20000<br>6KTL3 - 12000 | Width (mm)                    | 425                         |
| AC-nominal output power     | 10KTL3 - 11000<br>6KTL3 - 6600  | Height (mm)                   | 387                         |
| Country of manufacture      | China                           | Depth (mm)                    | 10KTL3 - 178<br>6KTL3 - 147 |
| Number of MPPT              | 2                               | Weight (kg)                   | 10KTL3 - 14<br>6KTL3 - 12.5 |

### BATERKY

|                     |             |                          |          |
|---------------------|-------------|--------------------------|----------|
| Product ref.        | ARK 2.5H-A1 | Max. depth of discharge  | 90%      |
| Width               | 650 mm      | Nominal battery capacity | 2.56 kWh |
| Height              | 200 mm      | Max. input voltage DC    | 51.2 V   |
| Depth               | 250 mm      | Usable battery capacity  | 2.3 kWh  |
| Number of phases    | 3           | Series                   | ARK      |
| Ambient temperature | -10 +55 °C  | Made in                  | China    |
| Type of voltage     | DC          | Units per pallet         | 12       |

### PANELY

|                  |         |                               |               |
|------------------|---------|-------------------------------|---------------|
| Product ref.     | JaSolar | Type                          | Mono PERC     |
| STC Power Rating | 460W    | Output Terminal Type          | MC Type 4     |
| Peak Efficiency  | 20.6%   | Output Cable Wire Length      | 1,200mm       |
| Power Tolerances | 0%/+5%  | Frame Color / Backsheet Color | Clear / White |
| Imp              | 11.45A  | Length                        | 2,120mm       |
| Vmp              | 42.13V  | Width                         | 1,052mm       |
| Isc              | 10.92A  | Depth                         | 40mm          |
| Voc              | 50.01V  | Weight                        | 25.0kg        |

## TECHNICKÉ PARAMETRE

### MENIČ

|                             |                  |                               |                 |
|-----------------------------|------------------|-------------------------------|-----------------|
| SKU                         | SPH 10KTL3 BH-UP | Degree of protection (IP)     | IP66            |
| DC Switch                   | Yes              | Suitable for outdoor mounting | Yes             |
| Warranty in Years           | 10               | Surge protection              | Type II DC & AC |
| Inverter type               | String           | Display                       | Yes             |
| Smart                       | Hybrid           | WiFi                          | Optional        |
| Number of phases            | 3 phase          | Ethernet                      | Optional        |
| Max. DC- input capacity (W) | 15000            | Width (mm)                    | 505             |
| AC-nominal output power     | 10000            | Height (mm)                   | 453             |
| Country of manufacture      | China            | Depth (mm)                    | 198             |
| Number of MPPT              | 2                | Weight (kg)                   | 30              |

### BATERKY

|                     |             |                          |          |
|---------------------|-------------|--------------------------|----------|
| Product ref.        | ARK 2.5H-A1 | Max. depth of discharge  | 90%      |
| Width               | 650 mm      | Nominal battery capacity | 2.56 kWh |
| Height              | 200 mm      | Max. input voltage DC    | 51.2 V   |
| Depth               | 250 mm      | Usable battery capacity  | 2.3 kWh  |
| Number of phases    | 3           | Series                   | ARK      |
| Ambient temperature | -10 +55 °C  | Made in                  | China    |
| Type of voltage     | DC          | Units per pallet         | 12       |